

Specification & Technical Data Sheet

Part Number: RWC-122C

12-02 NS CMR - GRAY

1.	Conductor	
	AWG Size:	12
	V Type:	19 Strand Bare Copper
2.	Insulation	
	Ø Material:	PVC
	Wall Thickness:	0.012"
	Color Code:	1-Black; 2-White
3.	Assembly	
	Cable Lay Length:	4.50" LHL (2.66 Tw/Ft)
	Shield:	Non
	Orain:	N/A
	Ø Braid:	
4.	Jacket	
	Q Material:	PVC
	Wall Thickness:	0.025"
	Oiameter:	0.285"
	Color:	Gray
	Q Ripcord:	Yes
	Weight:	62.0000 lbs/Mft.
5.	Markings	
	C Type:	Inkjet Printer
	Q Legend:	Sequential Foot Markers; UL Standard Legend; Riser Rated
	Footage Markers	Yes
6.	Electricals	
	Impedance:	Ω/Mft.
	Capacitance:	32 pF/ft +/- 10%
	 Cupucituritee. 	52 pi/ic i/ 10/0

7. Standards

- UL listed as type CL3R per UL standard 13 and as type FPLR 75°C per UL standard 1424
- All materials used in the manufacture of this cable are RoHS II & REACH compliant
- Maximum Operating Voltage: 300V RMS
- Made in the USA