

Specification & Technical Data Sheet

Part Number: RWC-142C

14-02 NS CMR - GRAY

1.	Conductor	
	AWG Size:	14
	V Type:	19 Strand Bare Copper
2.	Insulation	
	Q Material:	PVC
	Wall Thickness:	0.012"
	Color Code:	1-Black; 2-White
3.	Assembly	
	Cable Lay Length:	2.75" LHL (4.36 Tw/Ft)
	Shield:	Non
	Orain:	N/A
	Sraid:	
4.	Jacket	
	Material:	PVC
	Wall Thickness:	0.022"
	Oiameter:	0.240"
	Color:	Gray
	Q Ripcord:	Yes
	Weight:	42.0000 lbs/Mft.
5.	Markings	
	C Type:	Inkjet Printer
	Q Legend:	Sequential Foot Markers; UL Standard Legend; Riser Rated
	Footage Markers	: Yes
6.	Electricals	
	Impedance:	Ω/Mft.
	Capacitance:	29 pF/ft +/- 10%
	OC Resistance:	2.73 Ω/Mft. @ 20°C

7. Standards

- UL listed as type CL3R per UL standard 13 and as type FPLR 75°C per UL standard 1424
- All materials used in the manufacture of this cable are RoHS II & REACH compliant
- Maximum Operating Voltage: 300V RMS
- Made in the USA