

## Specification & Technical Data Sheet

## Part Number: RWC-164C

## 16-04 NS CMR - GRAY

1.	Conductor AWG Size:	16
	🖗 Type:	19 Strand Bare Copper
2.	Insulation	
	Material:	PVC
	Wall Thickness:	0.010"
	Color Code:	1-Black; 2-Red; 3-White; 4-Green
3.	Assembly	
	Cable Lay Length	: 2.75" LHL (4.36 Tw/Ft)
	Shield:	Non
	Orain:	N/A
	Ø Braid:	
4.	Jacket	
	Material:	PVC
	Wall Thickness:	0.022"
	Oiameter:	0.230""
	Color:	Gray
	Q Ripcord:	Yes
	🥥 Weight:	49.0000 lbs/Mft.
5.	Markings	
	V Type:	Inkjet Printer
	Q Legend:	Sequential Foot Markers; UL Standard Legend; Riser Rated
	Footage Marker	
6.	Electricals	
	Impedance:	Ω/Mft.
	Capacitance:	28 pF/ft +/- 10%
	© DC Resistance:	4.35 Ω/Mft. @ 20°C

## 7. Standards

- UL listed as type CL3R per UL standard 13 and as type FPLR 75°C per UL standard 1424
- All materials used in the manufacture of this cable are RoHS II & REACH compliant
- Maximum Operating Voltage: 300V RMS
- Made in the USA