

## Specification & Technical Data Sheet

## Part Number: RWC-224C

## 22-04 NS CMR - GRAY

1.	Conductor	
	AWG Size:	22
	Version of the second secon	7 Strand Bare Copper
2.	Insulation	
	🖗 Material:	PVC
	Wall Thickness:	0.007"
	Color Code:	1-Black; 2-Red; 3-White; 4-Green
3.	Assembly	
	Cable Lay Length:	: 3.00" LHL (4.00 Tw/Ft)
	Shield:	Non
	🖗 Drain:	N/A
	Ø Braid:	
4.	Jacket	
	Ø Material:	PVC
	Wall Thickness:	0.015"
	Oiameter:	0.135"
	Color:	Gray
	Ripcord:	Yes
	Veight:	15.0000 lbs/Mft.
5.	Markings	
	V Type:	Inkjet Printer
	Q Legend:	Sequential Foot Markers; UL Standard Legend; Riser Rated
	Footage Marker	
6.	Electricals	
	Impedance:	Ω/Mft.
	mpedaneer	
	Capacitance:	23 pF/ft +/- 10%

## 7. Standards

- UL listed as type CL3R per UL standard 13 and as type FPLR 75°C per UL standard 1424
- All materials used in the manufacture of this cable are RoHS II & REACH compliant
- Maximum Operating Voltage: 300V RMS
- Made in the USA