

Specification & Technical Data Sheet

Part Number: RWC-228C

22-08 NS CMR - GRAY

1. Conductor

AWG Size: 22

Type: 7 Strand Bare Copper

2. Insulation

Material: PVCWall Thickness: 0.007"

Color Code: 1-Black; 2-Red; 3-White; 4-Green; 5-Brown; 6-Blue; 7-Orange; 8-Yellow

3. Assembly

Cable Lay Length: 2.25" LHL (5.33 Tw/Ft)

Shield: NonDrain: N/A

Braid:

4. Jacket

✓ Material: PVC
✓ Wall Thickness: 0.018"
✓ Diameter: 0.180""
✓ Color: Gray
✓ Ripcord: Yes

Weight: 27.0000 lbs/Mft.

5. Markings

Type: Inkjet Printer

Legend: Sequential Foot Markers; UL Standard Legend; Riser Rated

Footage Markers: Yes

6. Electricals

 \bigcirc Impedance: Ω/Mft.

Capacitance: 23 pF/ft +/- 10%
DC Resistance: 17.50 Ω/Mft. @ 20°C

7. Standards

UL listed as type CL3R per UL standard 13 and as type FPLR 75°C per UL standard 1424

All materials used in the manufacture of this cable are RoHS II & REACH compliant

Maximum Operating Voltage: 300V RMS

Made in the USA