

Specification & Technical Data Sheet

Part Number: RWC-AV222CS-RD

22-02 TINNED COPPER OAS CMR LINE LEVEL AUDIO - RED JACKET

1. Conductor

- AWG Size: 22
- Type: 7 Strand Tinned Copper

2. Insulation

- Material: Polypropylene
- Wall Thickness: 0.008"
- Color Code: 1-Black; 2-Red

3. Assembly

- Cable Lay Length: 2.00 LHL (6 tw/ft)
- Shield: Heat Fusible Aluminum/Mylar 100%
- Drain: 22awg 7 Strand Tinned Copper (inside)
- Braid:

4. Jacket

- Material: Pressure Extruded PVC
- Wall Thickness: 0.022"
- Diameter: 0.140"
- Color: Red
- Ripcord: No
- Weight: 15.0000 lbs/Mft.

5. Markings

- Type: Inkjet Printer
- Legend: ANALOG SINGLE CHANNEL AUDIO CABLE E171197 22 AWG CMR C(UL)US 75°C
MADE IN THE USA ROHS COMPLIANT FT-4
- Footage Markers: Yes

6. Electricals

- Impedance: 55.0 Ω /Mft.
- Capacitance: 27.60 pF/ft +/- 10%
- DC Resistance: 14.10 Ω /Mft. @ 20°C

7. Standards

- Cable suitable for installations under NEC (NFPA 70) article 800 guidelines
- UL listed as type CMR c(UL)us 75°C per UL standard 444
- All materials used in the manufacture of this cable are RoHS compliant
- Maximum Operating Voltage: 300V RMS
- Made in the USA

