

Specification & Technical Data Sheet

Part Number: RWC-P224CS-WH/GN

22-04 OAS CMP - NATURAL W/ GREEN STRIPE

1.	Ø	AWG Size:	22 7 Strand Bare Copper
	e	туре.	
2. Insulation			
	Q	Material:	Plenum
	Ø	Wall Thickness:	0.007"
	Ø	Color Code:	1-Black; 2-Red; 3-White; 4-Green
3.			
		Cable Lay Length:	
		Shield:	Shielded
	Q	Drain:	
	Ø	Braid:	
4.	Jacket		
	Ø	Material:	Plenum
		Wall Thickness:	0.015"
		Diameter:	0.135"
		Color:	White w/ Green Stripe
		•	Yes
	Ø	Weight:	17.0000 lbs/Mft.
5.	-		
			Inkjet Printer
		-	Sequential Foot Markers; UL Standard Legend; Plenum Rated
	©	Footage Markers:	Yes
6.			
			Ω/Mft.
		•	47 pF/ft +/- 10%
	Q	DC Resistance:	17.50 Ω/Mft. @ 20°C
	2. 3. 4.	Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Constructions Co	 ♥ Type: Insulation ♥ Material: ♥ Wall Thickness: ♥ Color Code: Assembly ♥ Cable Lay Length: ♥ Drain: ♥ Braid: Ø Drain: ♥ Braid: Jacket ♥ Material: ♥ Wall Thickness: ♥ Diameter: ♥ Color: ♥ Weight: Markings ♥ Type: ♥ Legend: ♥ Footage Markers: Electricals ♥ Impedance: ♥ Capacitance:

7. Standards

- UL listed as type FPLP 75°C per UL standard 1424 or CL3P per UL Standard 13, CMP per UL 444
- All materials used in the manufacture of this cable are RoHS II & REACH compliant
- Maximum Operating Voltage: 300V RMS
- Made in the USA