

Specification & Technical Data Sheet

Part Number: RWC-P224CS-WH/OR

22-04 OAS CMP - NATURAL W/ ORANGE STRIPE

1. Conductor

AWG Size: 22

Type: 7 Strand Bare Copper

2. Insulation

Material: PlenumWall Thickness: 0.007"

Color Code: 1-Black; 2-Red; 3-White; 4-Green

3. Assembly

Cable Lay Length:

Shield: Shielded

Drain:Braid:

4. Jacket

Material: PlenumWall Thickness: 0.015"Diameter: 0.135"

Color: White w/ Orange Stripe

Ripcord: Yes

Weight: 17.0000 lbs/Mft.

5. Markings

Type: Inkjet Printer

Legend: Sequential Foot Markers; UL Standard Legend; Plenum Rated

Footage Markers: Yes

6. Electricals

 \bigcirc Impedance: Ω/Mft.

Capacitance: 47 pF/ft +/- 10% DC Resistance: 17.50 Ω /Mft. @ 20°C

7. Standards

UL listed as type FPLP 75°C per UL standard 1424 or CL3P per UL Standard 13, CMP per UL 444

All materials used in the manufacture of this cable are RoHS II & REACH compliant

Maximum Operating Voltage: 300V RMS

Made in the USA

